

MongoDB - CRUD

Topics : [MongoDB](#)

Written on [December 30, 2023](#)

CRUD stands for Create, Read, Update, and Delete, which are the basic operations that can be performed on any persistent storage. MongoDB, being a NoSQL database, provides a flexible and powerful set of CRUD operations. Here's an overview of how CRUD operations are implemented in MongoDB:

1. Create (Insert):

To insert documents into a MongoDB collection, you use the `insertOne` or `insertMany` method.

Example - Insert a Single Document:

```
db.collection_name.insertOne({  
  field1: value1,  
  field2: value2,  
  // ... other fields  
});
```

Example - Insert Multiple Documents:

```
db.collection_name.insertMany([  
  { field1: value1, field2: value2 },  
  { field1: value3, field2: value4 },  
  // ... other documents  
]);
```

2. Read (Query):

To retrieve documents from a MongoDB collection, you use the `find` method.

Example - Find All Documents:

```
db.collection_name.find();
```

Example - Find Documents Matching a Condition:

```
db.collection_name.find({ field: value });
```

Example - Find Documents with Projections (selecting specific fields):

```
db.collection_name.find({}).project({ field1: 1, field2: 1, _id: 0 });
```

Example - Find One Document:

```
db.collection_name.findOne({ field: value });
```

3. Update:

To update documents in a MongoDB collection, you use the updateOne or updateMany method.

Example - Update a Single Document:

```
db.collection_name.updateOne(  
  { field: value },  
  { $set: { updated_field: new_value } }  
)
```

Example - Update Multiple Documents:

```
db.collection_name.updateMany(  
  { field: value },  
  { $set: { updated_field: new_value } }  
)
```

4. Delete:

To remove documents from a MongoDB collection, you use the deleteOne or deleteMany method.

Example - Delete a Single Document:

```
db.collection_name.deleteOne({ field: value });
```

Example - Delete Multiple Documents:

```
db.collection_name.deleteMany({ field: value });
```

Additional Notes:

- **Upsert:** The updateOne and updateMany methods can also be used with the upsert option to perform an update or insert if the document doesn't exist.

- **Atomic Operations:** MongoDB provides atomic operations at the document level. Updates are atomic on a single document, even if multiple fields are modified.
- **Aggregation Framework:** For complex data transformations or aggregations, MongoDB offers a powerful Aggregation Framework that allows you to pipeline multiple operations.

© Copyright [Aryatechno](#). All Rights Reserved. Written tutorials and materials by [Aryatechno](#)